

VINTAGE WOOD HD PORCELAIN TILE



VINTAGE WOOD HD PORCELAIN TILE



6" x 24" VINTAGE WOOD DUNE HD PORCELAIN TILE

VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD DUNE HD PORCELAIN TILE
62-700



6" x 24" VINTAGE WOOD DUNE HD PORCELAIN TILE
62-500



6" x 36" VINTAGE WOOD ASH HD PORCELAIN TILE
62-703



6" x 24" VINTAGE WOOD ASH HD PORCELAIN TILE
62-503



6" x 36" VINTAGE WOOD SADDLE HD PORCELAIN TILE
62-701



6" x 24" VINTAGE WOOD SADDLE HD PORCELAIN TILE
62-501

VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD SADDLE HD PORCELAIN TILE

VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD CINNAMON HD PORCELAIN TILE
62-702



6" x 24" VINTAGE WOOD CINNAMON HD PORCELAIN TILE
62-502



6" x 36" VINTAGE WOOD CARBON HD PORCELAIN TILE
62-704



6" x 24" VINTAGE WOOD CARBON HD PORCELAIN TILE
62-504

VINTAGE WOOD HD PORCELAIN TILE



6" x 36" VINTAGE WOOD CINNAMON HD PORCELAIN TILE

VINTAGE WOOD HD PORCELAIN TILE

PACKAGING INFORMATION

DESCRIPTION	ITEM CODE					LBS/BOX	PCS/BOX	SQFT/BOX	BOXES/SKID	SQFT/SKID
	DUNE	SADDLE	CINNAMON	ASH	CARBON					
6" x 24" VINTAGE WOOD HD PORCELAIN TILE	62-500	62-501	62-502	62-503	62-504	54.01	14	14	40	560.00
6" x 36" VINTAGE WOOD HD PORCELAIN TILE	62-700	62-701	62-702	62-703	62-704	46.00	8	12	39	468.00

GENERAL SPECIFICATIONS

DESCRIPTION	METHOD	UNIT	13" x 13"	18" x 18"
THICKNESS		mm – in	9 mm – 11/32"	9 mm – 11/32"
WATER ABSORPTION	EN ISO 10545-3	(%)	≤ 0.5	≤ 0.5
ABRASION RESISTANCE	EN ISO 10545-7	(PEI)	3 - 4*	3 - 4*
SCRATCH HARDNESS		(Mohs)	8	8
BREAKING STRENGTH	EN ISO 10545-4	(lbf)	≥ 350	≥ 350
CHEMICAL RESISTANCE	EN ISO 10545-13	(GL)	Class A – Resistant	Class A – Resistant
FROST RESISTANCE	EN ISO 10545-12		Resistant	Resistant
STATIC COEFFICIENT OF FRICTION (WET)	ASTM C-1028	(μ)	≥ 0.70	≥ 0.70
STATIC COEFFICIENT OF FRICTION (DRY)	ASTM C-1028	(μ)	≥ 0.70	≥ 0.70
DCOF (WET)	ANSI B101.3		≥ 0.50	≥ 0.50
SHADE VARIATION			V2	V2

* Additional abrasion resistance (pei) information.



6" x 36" VINTAGE WOOD CARBON HD PORCELAIN TILE